Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200. Standard must be consulted for specific requirements. OMB NO. 1218-0072

NFPA RATING

Health: 2
Flammability: 3
Reactivity: 0
Personal Protection: H

IDENTITY (As Used On Label And List) **1000 SEAM SEALER**

Section I

Manufacturer's Name: **Auto Vehicle Parts Co. (Au-ve-co Products)**	Emergency Telephone Number **1-800-354-9816**
Address (Number, Street, City, State, and Zip Code) **7 Sperti Drive, Covington, KY 41017**	Telephone Number for information **1-800-354-9816**
Signature of Preparer (optional)	Date Prepared

Section II - Hazardous Ingredients/Identity

Hazardous Components (Specific Chemical Identity: Common Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Toluene	**100 PPM**	**100 PPM**		**15-20%**
Xylene	**100 PPM**	**100 PPM**		**15-20%**
Rubber, Resin, Filler (Non-hazardous)				**60-70%**

V.O.C.: 2.75 lb./gal.

***Sara III**

DOT SHIPPING: ORM-D Consumer Commodity

Section III - Physical/Chemical Characteristics

Boiling Point **231° F**	Specific Gravity ($^{H}2^{O}$ = 1): **1.26**
Vapor Pressure (100°F) **53mm Hg.**	Melting Point: **N/A**
Vapor Density (AIR = 1) **Heavier Than Air**	Evaporation Rate:
Solubility in Water: **Insoluble**	(Butyl Acetate = 1) **Faster Than Water**

Appearance and Odor: **Beige Paste With Solvent Odor**

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits:	LEL	UEL
43°F		**Lower 1.0%**	**Upper 7.0%**

Extinguishing Media: **Class B extinguisher, Carbon Dioxide, Dry Chemical, Foam**

Special Fire Fighting Procedures:
Water spray can be used to cool containers exposed to fire. Clear area of unprotected personnel. Fire fighters are to wear self contained breathing apparatus and proper protection gear. Keep containers closed tightly. Isolate from heat, sparks, and open flames.

Unusual Fire and Explosion Hazards: Closed containers may explode when exposed to extreme heat.