



MATERIAL SAFETY DATA SHEET

PRODUCT NAME(S): 5 STAR QUICKBASE "D" SLOW BASEMAKER REDUCER
PRODUCT CODE: #5607-1D (GALLON)

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURED FOR: International Autobody Marketing Group
ADDRESS: 9188 San Salvador- Suite 105
Scottsdale, AZ 85258
EMERGENCY PHONE: Chemtrec (800)424-9300
INFORMATION PHONE: (602) 451-4451
D.O.T. Hazardous Class: Paint, Flammable Liquid UN 1263

SECTION II - HAZARDOUS INGREDIENTS/ SARA III INFORMATION

| REPORTABLE COMPONENTS | CAS NUMBER | VAPOR PRESSURE mm Hg @ temp | WEIGHT PERCENT |
|---|------------|--------------------------------|----------------|
| *N-BUTYL-ALCOHOL | 71-36-3 | 5.5mm Hg @ 68 F | 10% |
| PROPIONIC ACID | 590-01-2 | 3.4mm Hg @ 68 F | 0-10% |
| MINERAL SPIRITS | 8032-32-4 | 5.2mm Hg @ 68 F | 10-20% |
| PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE | 108-65-6 | 3.7mm Hg @ 68 F | 0-10% |
| DIISOBUTYL KETONE | 108-83-8 | 1.4mm Hg @ 68 F | 45-55% |
| 4,6 DIMETHYL 2 HEPTANONE | 19549-80-5 | 1.4mm Hg @ 68 F | 10-20% |
| METHYL PROPYL KETONE | 107-87-9 | 27mm Hg @ 68 F | 0-10% |

*Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL CHARACTERISTICS

| | |
|----------------------|-------------------|
| BOILING RANGE: | 213-325F. |
| VAPOR DENSITY: | Heavier than air |
| SOLUBILITY IN WATER: | Slight |
| WEIGHT % VOLATILE: | 15.3-76.0% |
| VOLUME % VOLATILE: | 19.4-80.9% |
| EVAPORATION RATE: | Slower than ether |
| VOC LBS/ GL: | 6.70 |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| | | | |
|-------------------------|---|-------------------------------|-----------|
| FLASH POINT(Closed cup) | 46 degrees F. | APPROXIMATE FLAMMABLE LIMITS: | 0.8-13.1% |
| EXTINGUISHING MEDIA: | Foam, Carbon Dioxide, Dry Chemical, Water Fog | | |

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment, including self contained breathing apparatus, is recommended. Water from fog nozzles may be used to cool closed containers to prevent pressure build up.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When heated above flashpoint, emits flammable vapors which, when mixed with air, can burn or become explosive. Fine mists or sprays may be flammable below the flash point.

SECTION V - REACTIVITY DATA

| | |
|---------------------------------------|----------------------------|
| STABILITY: | Stable |
| INCOMPATIBILITY (MATERIALS TO AVOID): | Strong oxidizing materials |
| HAZARDOUS DECOMPOSITION PRODUCTS: | CO,CO2, smoke |
| HAZARDOUS POLYMERIZATION: | Will not occur |

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause nose and throat irritation. Repeated and prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness, and loss of coordination are signs that solvent levels are too high. Individuals with breathing problems must not be exposed to this product. If affected by inhalation, remove to fresh air. If breathing difficulty persists, consult a physician.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause irritation or burning of the eyes. Repeated and prolonged skin contact may cause skin irritation or dermatitis. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash with soap and water. If irritation occurs, contact a physician.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Gastrointestinal distress. In the unlikely event of ingestion, call a physician immediately and have the names of all ingredients available.

HEALTH HAZARDS (ACUTE AND CHRONIC):

ACUTE: Dizziness, irritation of the respiratory track, weakness, nausea, or possible narcosis or even asphyxiation. May be accompanied by coughing or labored breathing.

CHRONIC: Reports have linked organic solvents with brain and nervous system damage. Misuse of this product by deliberately concentrating and inhaling the contents may be harmful or fatal.

CARCINOGENICITY: *NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: N/A PROPOSITION 65 STATEMENT: WARNING!* This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Do not use this product if you have chronic lung or breathing problems.

EMERGENCY AND FIRST AID PROCEDURES: If ingestion, or any type of overexposure or symptoms of overexposure occur during the use of this product, contact poison control center, emergency room or physician immediately; have material safety data sheet available.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition(sparks, flames, and hot surfaces). Avoid breathing vapors. Ventilate area. Remove with an inert absorbent and non-sparking tools.

WASTE DISPOSAL METHOD: Disposed in accordance with state, federal and local regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly closed in a cool, dry well ventilated area away from all possible ignition sources. Store large quantities of material in buildings designed for the storage of flammable liquids.

OTHER PRECAUTIONS: Employees should be trianed in safety measures that should be taken when using this product.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Avoid breathing vapors or spray mist. Wear a properly fitted respirator approved by NIOSH/MSHA (TC-23c)for use with paints during application and until all vapors are exhausted. In confined areas, or where continious spray operations are typical, or proper respirator fit is not possible, wear a positive-pressure supplied air respirator (TC-19c). In all cases follow respirator manufactures directions for respirator use. Do not allow anyone without protection in the painting area.

VENTILATION: Provide sufficient ventilation to keep contaminates below applicable OSHA requirements.

PROTECTIVE GLOVES: Neoprene gloves impervious to organic solvents recommended.

EYE PROTECTION: Use safety eyewear designed to protect against liquid splash.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Impervious coveralls recommended.

WORK/HYGIENIC PRACTICES: Eye wash and safety showers in the work place are recommended. Wash hands before eating and smoking.

SECTION IX - DISCLAIMER

The information contained in this safety data sheet is information from our suppliers and other sources. It is believed to be reliable. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility.

We appreciate your interest in 5 Star Autobody Products! For more information about these and other 5 Star Autobody Products or for the location of the 5 Star Distributor nearest you, contact us at:

5 Star Autobody Products
9188 San Salvador Suite 105
Scottsdale, AZ 85258
Phone: 1-87-REFINISH
eMail: info@autobodybrands.com